


HD HYUNDAI SOLAR MODULE

NI Series

Premium N-Type TOPCon Module

HiN-T590NI | HiN-T595NI | HiN-T600NI



23.23%
High Efficiency



High-End
TOPCon
Technology



Higher
Bifaciality



Long-Term
Reliability



Rooftop
Applications



For Commercial
& Utility
Applications


HD Hyundai's Warranty Provisions

12
YEARS

- 12-Year Product Warranty
- Materials and workmanship

30
YEARS

- 30-Year Performance Warranty
- First year degradation: 1%
- Linear warranty after initial year: with 0.4%p annual degradation, 87.4% is guaranteed up to 30years



*Refer to HD HES standard warranty for details.

Certification



- ISO 9001:2015: Quality Management System
- ISO 14001:2015: Environmental Management System
- ISO 45001:2018: Occupational Health and Safety Management System
- UL 61730: Photovoltaic (PV) module safety qualification (CSA)
- IEC 61701: Salt mist corrosion testing
- IEC 62716: Ammonia corrosion testing
- IEC 62804: Potential Induced Degradation (PID) testing
- IEC 60068-2-68: Sand and dust testing for environmental durability

Electrical Characteristics

HiN-TxxxNI		HiN-T590NI		HiN-T595NI		HiN-T600NI	
Item	Unit	BNPI		BNPI		BNPI	
Nominal output (Pmax)	W	590	654	595	659	600	665
Open circuit voltage (Voc)	V	51.9	51.9	52.1	52.1	52.3	52.3
Short circuit current (Isc)	A	14.47	16.03	14.53	16.10	14.59	16.17
Voltage at Pmax (Vmpp)	V	43.2	43.2	43.4	43.4	43.6	43.6
Current at Pmax (Impp)	A	13.66	15.14	13.72	15.22	13.77	15.26
Module efficiency	%	22.84		23.03		23.23	
Power Class Sorting	W	0 ~ +5					
Temperature coefficient of Pmax	%/°C	-0.30					
Temperature coefficient of Voc	%/°C	-0.25					
Temperature coefficient of Isc	%/°C	0.046					
Bifaciality	%	80±10					

*STC : Irradiance 1,000 W/m², cell temperature 25°C, AM=1.5 / Test uncertainty for Pmax ±3%; Voc ±3%; Isc ±3%
 **The electrical properties of BNPI are measured under the irradiance corresponding to 1000 W/m² on the module front and 135 W/m² on the module rear.

Additional Power Gain from rear side						
Pmpp gain	Pmpp [W]	Vmpp [V]	Impp [A]	Voc [V]	Isc [A]	
5%	625	43.4	14.41	52.1	15.26	
15%	684	43.4	15.78	52.1	16.71	
25%	744	43.4	17.15	52.1	18.16	

*Electrical characteristics with different rear power gain (reference to 595W)


Mechanical Characteristics

Dimensions	2,278mm (L) x 1,134mm (W) x 30mm (H) (89.7in x 44.7in x 1.2in)
Weight	31.5 kg (69.5lbs)
Solar Cells	N-Type TOPCon, 144 (6x24) monocrystalline 16BB half-cut bifacial cells
Output Cables	Cable : (+) 1,200mm(47.2in), (-) 1,200mm(47.2in) Connector : Stäubli MC4 genuine Connector / IP68
Junction Box	3-part, 3 bypass diodes, IP68 rated
Construction	Front : 2.0mm(0.08in) semi-tempered solar glass with high transmittance and anti-reflective coating Rear : 2.0mm(0.08in) semi-tempered solar glass
Frame	Anodized aluminum alloy

Shipping Configurations

Truck Type	53' Dry Van	Modules Per Pallet (pcs)	36
Pallets Per Truck	16	Modules Per Truck (pcs)	576

Module Diagram (unit : mm)



Installation Safety Guide

- Only qualified personnel should install or perform maintenance.
- Be aware of dangerous high DC voltage.
- Do not handle or install modules when they are wet.

Nominal Module Operation Temperature	44°C ± 2°C
Operating Temperature	-40°C~+85°C
Maximum System Voltage	DC 1,500 V
Maximum Reverse Current	30A
Maximum Test Load	Front 5,400Pa Rear 2,400Pa
Fire Performance	Type 29

I-V Curves (HiN-T595NI)

